



BEL HISTOIRE

Francoise 15x15

rett



| | |
|----------------|--|
| Collection: | BEL HISTOIRE |
| Color: | Francoise |
| Top finish: | Mat |
| Size: | 15x15cm (5.9x5.9 in) |
| Thickness: | 8mm |
| Material Type: | Porcelain - single firing - dry pressed ceramic tile |

TECHNICAL DATA

| | Standard test | Value required by UNE-EN-14411 | Avarage value |
|---|--|--|-------------------------------------|
| Dimensional features: | UNE-EN-ISO-10545-2 | | Conforms to the requisites |
| Water absorption: | UNE-EN-ISO-10545-3 | E>0.5% | Comply the norm |
| Bending strenght Modulus of rupture Breaking strenght | UNE-EN-ISO-10545-4 | >35Nw/mm ² >1300Nw | Comply the norm |
| Resistance to surface abrasion | UNE-EN-ISO-10545-7 | 3 | |
| Linear thermal expansion | UNE-EN-ISO-10545-8 | <9*10 ⁻⁶ /°C | Declared value |
| Thermal shock restistance | UNE-EN-ISO-10545-9 | Required | Stands the test |
| Cracking resistance | UNE-EN-ISO-10545-11 | Required | Stands the test |
| Frost restistance | UNE-EN-ISO-10545-12 | Required | Stands the test |
| Chemical restistance Domestic and swimming pool products Acids and alkalis of low concentration | UNE-EN-ISO-10545-13 | Class A Min class LB | |
| Resitance to stains | UNE-EN-ISO10545-14 | Min class 4 | |
| Friction coeficient Pendulum Ramp DCOF | UNE-ENV-12633 DIN51130 ANSI A137.1 | Declared value Declared value Declared value | Not apply Not apply Not apply |
| Resistance to fire | Decision 96/603/CE | | Not apply |

CE MARKING



CE Declaration of performance:
N° 001VV2019